



RG+ Landscape Adhesive

UPDATE

October 1st, 2024

Make sure that you have an up-to-date technical data sheet in hand by consulting our Web site: techniseal.com

Canada and U.S.A.: dial 1 800 465-7325

Others: dial (514) 523-8324 (Canada)

APPLICATIONS

- Construction of retaining walls, wall caps, pillar caps, step treads, planters, walkways. etc
- Applications with long open time (such as installation over long sections)
- Temporary repairs such as loose brick & stone
- For concrete pavers, slabs, retaining walls, stone, brick, block, masonry, wood, metal, timber, slate and most common building materials used in landscaping.

PROPERTIES

- All-around flexible and versatile
- Premium advanced elastomeric adhesive formula
- All-weather application - can be used on dry, wet or frozen surfaces (extrudes from -18 °C to 38 °C / 0 °F to 100 °F)
- Works well in extreme weather conditions (such as early spring / late fall) to provide a long lasting, durable bond.
- Flexible, durable bond resists weathering
- Unlike polyurethane adhesive, it can be scraped off without breaking substrates
- The professional strength formula is waterproof (not designed for continuous submersion)
- Low VOC

DESCRIPTION

TECHNISEAL RG+ Landscape Adhesive is an elastomeric resin-based compound specially formulated to construct concrete hardscapes. It provides a strong bond and resists the elements (water, frost, etc.), making it ideal for use in all weather conditions. Its professional strength formula will bond to the most common building materials used in landscaping. Remaining flexible under cold temperatures, it is ideal for constructing retaining walls or repairing such as loose brick & stone. It is most effective on dry surfaces and can also be used on wet or frozen surfaces.

The RG+ Adhesive meets or exceeds the following standards: ASTM D3498, APA AFG-01, ASTM C557

DIRECTIONS

Surface should be clean and ideally dry. Apply a maximum thickness of 1 cm (3/8"); join pieces together immediately with a slight twisting motion. If surface is wet or frozen, curing will take longer.

Cleaning of tools: Use mineral spirits.

COVERAGE

- A 300 ml tube, a 1 cm (3/8 in.) bead covers up to 4,5 m (15 ft.)

STORAGE

Product must be kept in its original, unopened and tightly sealed container, and stored in a dry and well ventilated place with controlled temperature (5 °C to 25 °C). Keep sheltered from weather and direct sunlight. In proper storage conditions, the product's shelf life is 2 years following production (see date on packaging).

PACKAGING

Adhesive	Product Code	Retail Size	Units per box	Boxes per Pallet	Units per Pallet
RG+	70971142 (141-791)	300 ml	12	108	1296

WARNING

For more information and advice on the proper handling, storage, and disposal of this product, please refer to the latest version of its Safety Data Sheet (SDS). This official document contains physical, ecological, and other important information pertaining to the safe usage of this product. Visit www.techniseal.com or call 1-800-465-7325 to request or find an up-to-date version of this product's Safety Data Sheet (SDS).

KEEP OUT OF REACH OF CHILDREN

TRANSPORT

For more information and advice on the proper handling and transportation of this product, please refer to the latest version of its Safety Data Sheet (SDS). Visit www.techniseal.com or call 1-800-465-7325 to request or find an up-to-date version of this product's Safety Data Sheet (SDS).

LIMITED WARRANTY

Techniseal® warrants this Adhesive against manufacturing defects. As Techniseal® has no control over surface preparation and product application, results cannot be guaranteed. The Techniseal® warranty is limited only to the replacement of a product proven to be defective, and will never cover the cost of labour. A proof of purchase will be required for any claim. Notice : User should make sure that this product meets their needs by carrying out a test under anticipated conditions of use. In the event that no test was carried out, the warranty won't apply.